



轴承	外形尺寸 (mm)				基本额定载荷 (kN)		极限转速(转/分钟)	质量 Kg
	d	D	B	rs min	动态(Cr)	静态(Cor)		
16001	12	28	7	0.3	5.1	2.39	26000	0.019
16002	15	32	8	0.3	5.6	2.83	22000	0.025
16003	17	35	8	0.3	6.8	3.35	20000	0.032
16004	20	42	8	0.3	7.9	4.5	18000	0.051
16005	25	47	8	0.3	8.35	5.1	15000	0.06
16006	30	55	9	0.3	11.2	7.35	13000	0.091
16007	35	62	9	0.3	11.7	8.2	12000	0.11
16008	40	68	9	0.3	12.6	9.65	10000	0.125
16009	45	75	10	0.6	12.9	10.5	9200	0.171
16010	50	80	10	0.6	13.2	11.3	8400	0.18
16011	55	90	11	0.6	18.6	15.3	7700	0.258
16012	60	95	11	0.6	20	17.5	7000	0.283
16013	65	100	11	0.6	20.5	18.7	6500	0.307
16014	70	110	13	0.6	24.4	22.6	6100	0.441
16015	75	115	13	0.6	25	24	5700	0.464
16016	80	125	14	0.6	25.4	25.1	5300	0.597
16017	85	130	14	0.6	25.9	26.2	5000	0.626
16018	90	140	16	1	33.5	33.5	4700	0.848
16019	95	145	16	1	34.5	35	4500	0.885
16020	100	150	16	1	35	36.5	4200	0.91
16021	105	160	18	1	52	50.5	4000	1.2
16022	110	170	19	1	57.5	56.5	3800	1.46

16000 系列

16024	120	180	19	1	63	63.5	3500	4100	1.56
16026	130	200	22	1.1	80	79.5	3200	3800	2.31
16028	140	210	22	1.1	82	85	3000	3500	2.45
16030	150	225	24	1.1	96.5	101	2800	3200	3.07
16032	160	240	25	1.5	99	108	2600	3000	3.64
16034	170	260	28	1.5	119	128	2400	2800	4.93
16036	180	280	31	2	117	134	2300	2700	6.49
16038	190	290	31	2	134	156	2100	2500	6.77
16040	200	310	34	2	142	160	2000	2400	8.68