



Bearing number	Dimension mm											load rating kN		Weight
	d	B	d _k	C1 _{max}	d ₂	G	h	l ₁ _{min}	l ₂	rs _{min}	a°	dynamic load	static load	kg
SAJ5	5	8	11.112	7	16	M5	33	20	41	0.3	7	2.3	2.5	0.011
SAJ6	6	9	12.7	7	18	M6	36	22	45	0.3	11	3.2	4	0.015
SAJ8	8	12	15.875	9	22	M8	42	25	53	0.3	14	5.3	7.5	0.03
SAJ10	10	14	19.05	11	26	M10	48	29	61	0.3	12	7.3	10.5	0.048
SAJ12	12	16	22.225	12	30	M12	54	33	69	0.3	13	8.5	13	0.076
SAJ14	14	19	25.4	14	34	M14	60	36	77	0.3	14	12	17	0.115
SAJ16	16	21	28.575	15	38	M16	66	40	85	0.3	15	16.5	21	0.159
SAJ18	18	23	31.75	17	42	M18x1.5	72	44	93	0.6	14	20	25.5	0.222
SAJ20	20	25	34.925	18	46	M20x1.5	78	47	101	0.6	14	23	30	0.292
SAJ22	22	28	38.1	20	50	M22x1.5	84	51	109	0.6	15	27.5	35.5	0.381